








## W6 W

6.5" PASSIVE SPEAKER, WHITE (PAIR)  
[100V|8Ω]

-  Low Impedance Input
-  100V Line Input
-  Ver./Hor. Installation
-  Easy Install
-  Bracket Included
-  Discreet Design

The W6 two-way loudspeakers with built-in 100V transformer and 8Ω power tap are perfect for both distributed and near-field applications in environments such as retail stores, restaurants, bars, churches and gyms. The low frequencies are reproduced by a 6.5" direct-radiating woofer with a polypropylene cone, while the high-frequency section is based on a titanium tweeter. The speaker's design with a waveguide improves dynamics and efficiency bringing out details in everything you listen to, while reducing reflections that can color the sound. A U-bracket is included and will support your installation on the wall or ceiling.

### Product Type

2-Way Passive Speaker (8Ω/100V)

### Frequency Response (-6dB)

70Hz - 18kHz

### Nominal Coverage (-6dB)

100° H x 100° V

### RMS Power

40W

### Program Power

80W

### Nominal Impedance

8Ω (low impedance mode)

### Sensitivity (1W, 1m)

88dB

### Maximum SPL (calculated)

104dB

### Transformer Taps 100V

3.75W | 7.5W | 15W | 30W

### Low Frequency Driver

6.5" Polypropylene Cone Woofer

### High Frequency Driver

1" Silk Dome Tweeter

### Input Connectors

Binding Posts

### Recommended Amplifier

A40 | A200 | MX120 | MX350

### Construction

High-grade Rugged Polypropylene

### IP Rating

Indoor Use

### Dimensions (WxHxD)

205 x 310 x 195mm (8" x 12.2" x 7.6")  
[W6W] | 205 x 345 x 225mm (8" x 13.5" x 8.8") [W6W + U-Bracket]

### Fixation

Wall U-Bracket (included)

### Net Weight

4kg (8.82lb) [W6W + U-Bracket]

### Shipping Weight

8.5kg (18.74lb)