




PFA15

ACTIVE FULL-RANGE SPEAKER / MONITOR



The PFA15 is an active 15" speakers engineered specifically for installations, musicians and DJs to deliver high output and dynamics, extreme linearity and fidelity at a very competitive price, making them an affordable solution for the professional market. Recommended for use in either fixed installations or mobile applications the PFA15 is effective both as a stage monitor or as a compact FOH system. This speaker employs premium-quality multi-plywood with a hardening, durable, and scratch-resistant coating, fully rotatable constant directivity HF horns to adjust HxV angle coverage and custom-made speaker drivers.

<p>Product Type Active Two-Way Speaker/Monitor</p>	<p>Frequency Response (-6dB) 54Hz - 18.000Hz</p>	<p>Nominal Coverage (-6dB) 90° x 60° user rotatable</p>
<p>Amplifier Technology 2 channel switched mode class AB with DSP</p>	<p>LF Section Power RMS: 400W / Program: 540W / Peak: 1080W</p>	<p>HF Section Power RMS: 100W / Program: 135W / Peak: 270W</p>
<p>DSP Technology Controlled Networkable DSP 24bit/48kHz</p>	<p>DSP Adjustable Parameters 6 PEQ, delay, HPF, LPF, Bass Enhancer, Level, Polarity, Mute</p>	<p>DSP Presets 6 Factory and 2 User, selectable via software or rear panel switch</p>
<p>Control Type Via RS485 and suplied software "SOUNDWARE"</p>	<p>Maximum SPL (calculated) 126dB / 132dB (Full-Space)</p>	<p>Low Frequency Driver 1 x 15" (380mm) / 3" (76mm) voice coil, custom speaker</p>
<p>High Frequency Driver 1 x 1" (25mm) exit / 1.75" (44mm) voice coil, custom compression driver</p>	<p>Power Input 90V - 245V</p>	<p>Mains Connector Signal: 2 x XLR ; Power: 2 x powerCON</p>
<p>Power Consumption 550W</p>	<p>Dimensions (WxHxD) 431 x 654 x 440 mm</p>	<p>Net Weight 25.7kg</p>
<p>Shipping Weight 28.5kg</p>		