

LA122 Architectural Specifications

The loudspeaker shall be a 2-way line array element comprising of one high power 12" (304.8 mm) reflex loaded low frequency transducer with a neodymium ring magnet assembly and two neodymium compression drivers.

The low frequency transducer shall be constructed on a rigid metal frame, with a 3" (76 mm) copper voice coil. The high frequency compression driver shall have a 1.4" (35.6 mm) horn throat diameter with a 3" (76 mm) voice coil and shall project its sound through a waveguide with a symmetrical horn mouth.

The typical characteristics of a unit shall be; the directivity pattern shall be 90° horizontal by 8° at minus 6 dB; the frequency response shall be from 58 Hz to 19 kHz with a low frequency extension of 48 Hz at minus 10 dB; the maximum output shall be 129 dB with a peak output of 135 dB measured in full space.

The cabinet shall be constructed of 15 mm laminated birch plywood finished with a durable semi-matte black textured polyurethane coating. The rear of the cabinet shall have two NL4 connectors. It shall have integrated 4-point rigging system for arraying with multiple cabinets with an adjustable splay angle of 0° to 8° in 1° intervals. External dimension of the complete unit shall be 602 x 350 x 465 mm (23.7" x 13.8" x 18.3") and it shall have a net weight of 33 kg (72.8lb).

The loudspeaker shall be the LA122 by NEXT-proaudio.