

# LAs15

## Ultra-Compact Reflex Subwoofer



### TECHNICAL SPECIFICATIONS



- Ultra-Compact Subwoofer
- Fast, simple Integrated Rigging hardware
- Small, Versatile, Loud
- High SPL and Low Distortion
- M20 Pole Mount

### OVERVIEW

The LAs15 is the passive subwoofer model that completes the range of LA26 Line Array System. The subwoofer houses a long excursion B&C 15" driver powered by the N-RAK6 or N-RAK12. This unit is capable of delivering up to 2000W with a magnificent precision and punch at incredible SPL, combining optimized acoustic, electro-acoustic and electronic solutions to maximized efficiency.

LAs15 subwoofer is versatile enough to address any fixed installation or rental application. Sound Designers, Engineers or Integrators can choose from standard or cardioid configurations, creating a variety of symmetric and asymmetric directivity patterns adapted to each specific solution. The LAs15 can be hung with LA26 which becomes a perfect solution for any indoor/outdoor venue.

Technical Data	
Speaker Type:	Ultra-Compact Reflex Subwoofer
Acoustical Data	
Frequency Response (-6dB):	44Hz - X-over
Sensitivity (1W@1m):	102dB (Half-space)
Calculated Max. SPL (Cont/Peak):	135dB/138dB (Half-space)
Drivers	
Low Frequency:	1 x 15" (380mm)/4" (100mm) VC, long excursion, B&C custom speaker
Electrical Data	
Program/Peak Power LF:	2000W/4000W (10ms)
Nominal Impedance:	4
Connectors:	1 x Neutrik NL4
Enclosure	
Dimensions (WxHxD):	499 x 475 x 580mm
Net Weight:	40kg